

Polyend Anywhere
Portable Power Supply
User Manual

Polyend Anywhere Portable Power Supply

The world of music is instinctively connected with the organic world that surrounds us. Work on your musical workflow on the go. Make ambient in the depths of a forest, or techno atop a hill or just on a couch. No matter where you want to play and compose Polyend Anywhere is a real inspiration enabler.

Polyend Anywhere makes it possible to run a defined eurorack setup powered from a portable USB power bank (**not included**), completely free from a wall power outlet! Power bank of a let's say 20,000mAh will power multiple modules for a few hours and true portability is achieved! Perfect for a walk in the woods or a session in a downtown park. If you seek musical inspiration in places far from any power grid, you're all set now.

Polyend Anywhere features

- Width: 4HP.
- +12V/+5V/-12V.
- Max. output current allows powering up the individual buses at 1A for 12VDC, 1A for -12V.
- +5VDC bus amperage is dependent upon the used power bank performance.
- A total number of modules powered (or the max. output current) depends on two factors:
 - Power bank efficiency (recommended min. 2.4A/5V).
 - Power consumption distribution for a specific setup of modules for all three buses +12V/-12V/+5V.



What's in the box

- Anywhere module.
- Ribbon cable with ten outputs.
- USB cable.
- Manual.
- Two screws.

Important notes

Recommended minimum power bank efficiency is 2.4A/5V.

For the best performance use the USB and ribbon cables provided with the Anywhere module.

Do not connect Anywhere module to any power buses in your eurorack cases with a ribbon cable! There's a risk of conflict and a short circuit with the case power supply. It may damage the module or your power supply.

Limited warranty

Polyend warrants this product, to the original owner, to be free of defects in materials or construction for one year from the date of purchase. Proof of purchase is necessary when a warranty claim is made. Malfunctions resulting from improper power supply voltages, backwards or faulty cable connection, abuse of the product or any other causes determined by Polyend to be the fault of the user are not covered by this warranty (normal services rates will be applied). All defective products will be replaced or repaired at the discretion of Polyend. Products must be returned directly to Polyend with the customer paying the shipping cost. Polyend implies and accepts no responsibility for harm to a person or apparatus through the operation of this product. Please contact hello@polyend.com for return to manufacturer authorization, or any other technical questions/concerns.